

Listing of Claims:

1. (currently amended) A character recognition method for accurately constructing a result string the method comprising the steps of:

- generating a digital representation of an input string including characters;
- generating a result set for each character in the input string, each result set including a plurality of candidate characters and a plurality of associated confidence indications indicative of successful recognition of the corresponding candidate character;
- creating a candidate string by concatenating a candidate character with a most favorable corresponding confidence indication from each result set;
- selecting a plurality of character types;
- for each selected character type, creating a candidate string by concatenating a candidate character with a most favorable corresponding confidence indication of the selected character type from each result set;
- reviewing each candidate string to determine if all candidate characters of a candidate string conform to the same character type;
- removing from further consideration any candidate string that includes candidate characters conforming to different character types;
- for each created and remaining candidate string, combining the associated confidence indication for each concatenated candidate character to form a corresponding combined confidence indication; and
- selecting as the result string the created candidate string with a most favorable corresponding combined confidence indication and having all candidate characters conforming to a selected character type.

BEST AVAILABLE COPY

2. (original) The method of claim 1, wherein:
each confidence indication is numeric; and
the most favorable corresponding combined confidence indication has a greatest combined value.
3. (original) The method of claim 2, wherein the combined numeric value is a weighted average.
4. (original) The method of claim 1 further comprising the step of: if there is no candidate character in a result set for a character type, extracting a substitute candidate character of a different character type and ascribing a substitute associated confidence indication for the substitute candidate character.
5. (original) The method of claim 1 wherein at least one of the selected character types includes a plurality of subset character types.
6. (original) The method of claim 5 wherein the at least one of the selected character types further includes a pattern for positioning the candidate characters of the plurality of subset character types in the corresponding created candidate string.

BEST AVAILABLE COPY

7. (new) A computer readable medium having computer instruction code for performing a method of character recognition to accurately construct a result string, the method comprising:

generating a digital representation of an input string including characters;

generating a result set for each character in the input string, each result set including a plurality of candidate characters and a plurality of associated confidence indications indicative of successful recognition of the corresponding candidate character;

creating a candidate string by concatenating a candidate character with a most favorable corresponding confidence indication from each result set;

selecting a plurality of character types;

for each selected character type, creating a candidate string by concatenating a candidate character with a most favorable corresponding confidence indication of the selected character type from each result set;

reviewing each candidate string to determine if all candidate characters of a candidate string conform to the same character type;

removing from further consideration any candidate string that includes candidate characters conforming to different character types;

for each created and remaining candidate string, combining the associated confidence indication for each concatenated candidate character to form a corresponding combined confidence indication; and

selecting as the result string the created candidate string with a most favorable corresponding combined confidence indication and having all candidate characters conforming to a selected character type.

BEST AVAILABLE COPY

8. (new) The computer readable medium of claim 7, wherein:
each confidence indication is numeric; and
the most favorable corresponding combined confidence indication has a greatest combined value.
9. (new) The computer readable medium of claim 8, wherein the combined numeric value is a weighted average.
10. (new) The computer readable medium of claim 7, wherein the method further comprises:
if there is no candidate character in a result set for a character type, extracting a substitute candidate character of a different character type and ascribing a substitute associated confidence indication for the substitute candidate character.
11. (new) The computer readable medium of claim 7, wherein at least one of the selected character types includes a plurality of subset character types.
12. (new) The computer readable medium of claim 11 wherein the at least one of the selected character types further includes a pattern for positioning the candidate characters of the plurality of subset character types in the corresponding created candidate string.

BEST AVAILABLE COPY

13. (new) A character recognition method for accurately constructing a result string, the method comprising the steps of:

- generating a digital representation of an input string including characters;
- generating a result set for each character in the input string, each result set including a plurality of candidate characters and a plurality of associated confidence indications;
- creating a candidate string by concatenating a candidate character with a most favorable corresponding confidence indication from each result set;
- selecting a plurality of character types;
- for each selected character type, creating a candidate string by concatenating a candidate character of the selected character type from each result set;
- reviewing each candidate string to determine if all candidate characters of a candidate string conform to the same character type;
- removing from further consideration any candidate string that includes candidate characters conforming to different character types;
- for each created and remaining candidate string, combining the associated confidence indication for each concatenated candidate character to form a corresponding combined confidence indication; and
- selecting as the result string the created candidate string with a most favorable corresponding combined confidence indication and having all candidate characters conforming to a selected character type.

14. (new) The method of claim 13, wherein:

- each confidence indication is numeric; and

BEST AVAILABLE COPY

the most favorable corresponding combined confidence indication has a greatest combined value.

15. (new) The method of claim 14, wherein the combined numeric value is a weighted average.

16. (new) The method of claim 13, further comprising the step of: if there is no candidate character in a result set for a character type, extracting a substitute candidate character of a different character type and ascribing a substitute associated confidence indication for the substitute candidate character.

17. (new) The method of claim 13, wherein at least one of the selected character types includes a plurality of subset character types.

18. (new) The method of claim 17, wherein the at least one of the selected character types further includes a pattern for positioning the candidate characters of the plurality of subset character types in the corresponding created candidate string.

BEST AVAILABLE COPY